



ORG TAN ASF

ORG TAN ASF is a chrome aluminium complex syntan

Aspect : Light Bluish Green powder
pH : In 10% aqueous solution, 3.0 – 4.0
Cr₂O₃ : 10.0 ± 1.0%
Al₂O₃ : 10.0 ± 1.0%

PROPERTIES

ORG TAN ASF

- When used in chrome tanning imparts smooth, fine and soft grain.
- Has got full tanning properties and can be used for fringe level tannage of pickled skins as it gives rapid penetration of chrome and develops a fine grain. The tannage can be completed by normal chrome tanning using a conventional or self-basifying system.
- Is used in retanning process to produce full and soft leather with tight fibres and fine grain, suitable to give good buffing effect, short nap on nubuck, suede and corrected grain leather.
- imparts enriched brilliancy in dyeing.

APPLICATIONS

During Chrome tanning: After pickling

(All % on pelt weight)

ORG TAN ASF	4.0%	1 hr
Basic Chrome Sulphate	4.0%	1 hr
Orgcide TC 30	0.05%	1 hr
Orgfix CR	0.4%	7 hrs
End pH	3.8 – 4.0	

During Rechroming

(All % on shaved wt.)

Water	100%	
ORG TAN ASF	3-5%	45'

In Semi Chrome

ORG TAN ASF can be used up to 5% on EI shaved weight along With 5% Basic Chrome Sulphate (BCS)

SHELF LIFE

In cool & dry condition it can be stored for more than 2 years, but when kept in humid and elevated temperatures some caking may be observed. Technical suggestions without any obligation.